

Beam Power Tube

NOVAR TYPE

For Horizontal-Deflection-Amplifier
Service in Black-and-White TV Receivers

Electrical:

Heater Ratings and Characteristics:


Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	1.200	amp
Peak heater-cathode voltage:		
Heater negative with respect to cathode	200	max. volts
Heater positive with respect to cathode	200	max. ^a volts
Direct Interelectrode Capacitances (Approx.): ^b		
Grid No.1 to plate.	0.26	pf
Input: G1 to (K, G3, G2, H)	15.0	pf
Output: P to (K, G3, G2, H)	6.5	pf

Mechanical:

Operating Position.	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length.	3.505"
Seated Length	2.875" to 3.125"
Diameter.	1.438" to 1.562"
Dimensional Outline.	See General Section
Bulb.	T12
Cap.	Skirted Miniature (JEDEC C1-2 or C1-3)
Base.	Large-Button Novar 9-Pin with Exhaust Tip (JEDEC No. E9-88)

Basing Designation for BOTTOM VIEW. 9QK

- Pin 1-Grid No.2
- Pin 2-Grid No.1
- Pin 3-Cathode,
 Grid No.3
- Pin 4-Heater
- Pin 5-Heater
- Pin 6-Grid No.1
- Pin 7-Grid No.2
- Pin 8-No Internal
 Connection
- Pin 9-Do Not Use
 Cap-Plate

Characteristics, Class A₁ Amplifier:

	Triode Connection	Pentode Connection	
Plate Voltage	150	60	250 volts
Grid-No.2 Voltage	150	150	150 volts
Grid-No.1 Voltage	-22.5	0	-22.5 volts
Mu-factor, Grid No.2 to Grid No.1	4.4	-	- -
Plate Resistance (Approx.)	-	-	15000 ohms
Transconductance.	-	-	7100 μmhos



6GJ5A

	Triode Connection	Pentode Connection		
Plate Current	-	390°	70	ma
Grid-No.2 Current	-	32°	2.1	ma
Grid-No.1 Voltage (Approx.) for plate ma = 1.	-	-	-42	volts

HORIZONTAL-DEFLECTION AMPLIFIER

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^d

DC Plate-Supply Voltage	770	max.	volts
Peak Positive-Pulse Plate Voltage ^e	6500	max.	volts
Peak Negative-Pulse Plate Voltage	1500	max.	volts
DC Grid-No.2 (Screen-Grid) Voltage.	220	max.	volts
DC Grid-No.1 (Control-Grid) Voltage	-55	max.	volts
Peak Negative-Pulse Grid-No.1 Voltage	330	max.	volts
Cathode Current:			
Peak.	550	max.	ma
Average	175	max.	ma
Grid-No.2 Input	3.5	max.	watts
Plate Dissipation ^f	17.5	max.	watts
Bulb Temperature (At hottest point on bulb surface).	240	max.	°C

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For grid resistor-bias operation. 1 max. megohm

^a The dc component must not exceed 100 volts.

^b Without external shield.

^c This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.


^d As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

^e This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

^f An adequate bias resistor or other means is required to protect the tube in the absence of excitation.



AVERAGE CHARACTERISTICS



RADIO CORPORATION OF AMERICA
Electronic Components and Devices

Harrison, N. J.

DATA 2
10-64