




75

75

**DUPLEX-DIODE HIGH-MU TRIODE**

| | | |
|---|---|------------------|
| Heater | Coated Unipotential Cathode | |
| Voltage | 6.3 | a-c or d-c volts |
| Current | 0.3 | amp. |
| Direct Interelectrode Capacitances (approx.): | | |
| <i>Triode Unit</i> | | |
| Grid to Plate | 1.7 | μf |
| Grid to Cathode | 1.7 | μf |
| Plate to Cathode | 3.8 | μf |
| Overall Length | 4-9/32" to 4-17/32" | |
| Seated Height | 3-21/32" to 3-29/32" ← | |
| Maximum Diameter | 1-9/16" | |
| Bulb | ST-12 | |
| Cap | Small Metal | |
| Base | Small 6-Pin | |
| Pin 1-Heater |  | Pin 5-Cathode |
| Pin 2-Triode Plate | | Pin 6-Heater |
| Pin 3-Diode Plate #2 | | Cap -Triode Grid |
| Pin 4-Diode Plate #1 | | |
| Mounting Position | | Any |

BOTTOM VIEW (6G)

AMPLIFIER

Plate Voltage 250 max. volts

Characteristics and Curves are the same as for Type 6SQ7. For Typical Operating Conditions see RESISTANCE-COUPLED AMPLIFIER CHART. Diode Curves under Type 6B7 also apply to the 75.

■ In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.

← Indicates a change.

Sept. 2, 1941

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

DATA

75



75

AVERAGE CHARACTERISTICS TRIODE UNIT

$E_f = 6.3$ VOLTS

PLATE VOLTS = 250

