




ELECTRONIC  
**INNOVATIONS**  
IN ACTION

**TUBES**

# 7462 METAL-CERAMIC TRIODE



## DESCRIPTION AND RATING

The 7462 is a high-mu triode of ceramic-and-metal planar construction primarily intended for radio-frequency amplifier service from low frequencies into the ultra-high-frequency range. It is similar to the 7077 in characteristics but differs in having terminal lugs for use in print-board circuits.

### GENERAL

#### ELECTRICAL

Cathode—Coated Unipotential  
Heater Characteristics and Ratings

Heater Voltage, AC or DC*	6.3 ± 0.3	Volts
Heater Current†	0.24	Amperes

Direct Interelectrode Capacitances‡

Grid to Plate: (g to p)	1.25	pf
Input: g to (h+k)	1.8	pf
Output: p to (h+k)	0.032	pf
Heater to Cathode (h to k)	1.5	pf

#### MECHANICAL

Mounting Position—Any  
See Outline Drawing on page 2 for dimensions and electrical connections.

### MAXIMUM RATINGS

#### ABSOLUTE-MAXIMUM VALUES

Plate Voltage	250	Volts
Positive Peak and DC Grid Voltage	0	Volts
Negative Peak and DC Grid Voltage	50	Volts
Plate Dissipation	1.1	Watts
DC Cathode Current	11	Milliamperes

Heater-Cathode Voltage	
Heater Positive with Respect to Cathode	50 Volts
Heater Negative with Respect to Cathode	50 Volts
Grid-Circuit Resistance, with Fixed Bias§	
	0.01 Megohms
Bulb Temperature at Hottest Point¶	
	250 C

Absolute-Maximum ratings are limiting values of operating and environmental conditions applicable to any electron tube of a specified type as defined by its published data and should not be exceeded under the worst probable conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube, making no allowance for equipment variations, environmental variations, and the effects of changes in operating conditions due to variations in the characteristics of the tube under consideration and of

all other electron devices in the equipment.

The equipment manufacturer should design so that initially and throughout life no absolute-maximum value for the intended service is exceeded with any tube under the worst probable operating conditions with respect to supply-voltage variation, equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of the tube under consideration and of all other electron devices in the equipment.

### CHARACTERISTICS AND TYPICAL OPERATION

#### AVERAGE CHARACTERISTICS


Plate Voltage	150	Volts
Grid Voltage	+6.0	Volts
Cathode-Bias Resistor	910	Ohms
Amplification Factor	94	

Plate Resistance, approximate	9000	Ohms
Transconductance	10500	Micromhos
Plate Current	7.2	Milliamperes
Grid Voltage, approximate		
I <sub>b</sub> = 100 Microamperes	-2.4	Volts



**FOOTNOTES**

- \* The equipment designer should design the equipment so that heater voltage is centered at the specified bogey value, with heater supply variations restricted to maintain heater voltage within the specified tolerance.
- † Heater current of a bogey tube at  $E_f = 6.3$  volts.
- ‡ Without external shield.
- § If a cathode bias resistor is used, the grid-circuit resistance may be as high as  $(10,000 + 100 R_k + R_L)$  ohms, where  $R_k$  is the value of the cathode-bias resistor in ohms and  $R_L$  is the value of the plate-load resistor in ohms.
- ¶ For applications where long life is a primary consideration, it is recommended that the envelope temperature be maintained below 175 C.



**NOTE:** Maximum eccentricity of insulators 0.010 in. from center line.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or

elements. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

**INITIAL CHARACTERISTICS LIMITS**

	Min.	Bogey	Max.	
Heater Current				
$E_f = 6.3$ volts	222	240	258	Milliamperes
Plate Current				
$E_f = 6.3$ volts, $E_b = 150$ volts, $R_k = 82$ ohms (bypassed)	4.5	7.5	11	Milliamperes
Transconductance				
$E_f = 6.3$ volts, $E_b = 150$ volts, $E_c = +6$ volts, $R_k = 910$ ohms (bypassed)	8000	10500	13000	Micromhos
Amplification Factor				
$E_f = 6.3$ volts, $E_b = 150$ volts, $E_c = +6$ volts, $R_k = 910$ ohms (bypassed)	65	94	115	

### INITIAL CHARACTERISTICS LIMITS (Continued)

	Min.	Bogey	Max.	
<b>Transconductance Change with Heater Voltage</b>				
Difference between transconductance at $E_f = 6.3$ volts and transconductance at $E_f = 6.0$ volts (other conditions the same) expressed as a percentage of transconductance at $E_f = 6.3$ volts . . . . .			15	Percent
<b>Grid Voltage Cutoff</b>				
$E_f = 6.3$ volts, $E_b = 150$ volts, $I_b = 100 \mu a$ . . . . .		-2.4	-4.5	Volts
<b>Interelectrode Capacitances</b>				
Grid to Plate: (g to p) . . . . .	1.05	1.25	1.45	pf
Input: g to (h+k) . . . . .	1.25	1.8	2.25	pf
Output: p to (h+k) . . . . .	0.013	0.032	0.045	pf
Heater to Cathode: (h to k) . . . . .	1.1	1.5	1.9	pf
<b>Heater-Cathode Leakage Current</b>				
$E_f = 6.3$ volts, $E_{hk} = 100$ volts				
Heater Positive with Respect to Cathode . . . . .			20	Microamperes
Heater Negative with Respect to Cathode . . . . .			20	Microamperes
<b>Interelectrode Leakage Resistance</b>				
$E_f = 6.3$ volts. Polarity of applied d-c interelectrode voltage is such that no cathode emission results.				
Grid to All of 100 volts d-c . . . . .	100			Megohms
Plate to All at 300 volts d-c . . . . .	100			Megohms
<b>Grid Emission Current</b>				
$E_f = 7.0$ volts, $E_b = 100$ volts, $E_{cc} = -10$ volts, $R_g = 0.1$ meg . . . . .			2.0	Microamperes

### SPECIAL PERFORMANCE TESTS

#### Low Frequency Vibrational Output

Statistical sample is subjected to vibration in each of two planes at 40 cps, with peak acceleration 15 G. Tube is operated with  $E_f = 6.3$  volts,  $E_{bh} = 150$  volts,  $R_k = 82$  ohms (bypassed),  $R_L = 10000$  ohms . . . . .

10 Millivolts RMS

#### Variable Frequency Vibrational Output

Statistical sample is subjected to vibration according to the procedure given below. Tube is operated with  $E_f = 6.3$  volts,  $E_{bb} = 150$  volts,  $R_k = 82$  ohms (bypassed)  $R_L = 10000$  ohms . . . . .

15 Millivolts RMS

The variable-frequency vibration test shall be performed as follows:

1. The frequency shall be increased from 100 to 2000 cps with approximately logarithmic progression in  $3 \pm 1$  minutes. The return sweep (2000 to 100 cps) is not required.
2. The tube shall be vibrated with simple harmonic motion in each of two planes: first, parallel to the cylindrical axis; second, perpendicular to the cylindrical axis and parallel to a line through the major axis of a terminal lug. At all frequencies from 100 to 2000 cps, the total harmonic distortion of the acceleration waveform shall be less than 5%.
3. The peak acceleration shall be maintained at  $10 \pm 1.0$  G throughout the test.
4. The value of the alternating voltage produced across the load resistor ( $R_L$ ), as a result of the vibration, shall be measured with a suitable device having a response to the RMS value of the voltage to within  $\pm 0.5$  db of the response at 400 cps for the frequency range of 100 to 3000 cps, and having a band-pass filter with an attenuation rate of 24 db per octave below the low frequency cutoff point of 50 cps and above the high frequency cutoff point of 5000 cps. The meter shall have a dynamic response characteristic equivalent to or faster than a VU meter (operated in accordance with ASA Standard No. C16.5-1954).

#### Low Pressure Voltage Breakdown Test

Statistical sample tested for voltage breakdown at a pressure of 8 mm Hg, to simulate an altitude of 100,000 feet. Tubes shall not give visual evidence of flashover or corona when 300 volts RMS, 60 cps, is applied between the plate and grid terminals.

## DEGRADATION RATE TESTS

### Fatigue

Statistical sample vibrated for a total of six hours, three hours in each of two planes, at a peak acceleration of 10 G. Frequency is continuously varied from 30 cps to 2000 cps and back to 30 cps, with a period of ten minutes. Tubes are operated during the test with  $E_f = 6.3$  volts,  $E_b = 150$  volts, and  $R_k = 82$  ohms. Following the test, tubes are evaluated for low frequency vibrational output, heater-cathode leakage, heater current, and transconductance.

### Shock

Statistical sample subjected to 5 impact accelerations of approximately 450 G in each of four positions. The accelerating forces are applied by the Navy-type, High Impact (flyweight) Shock Machine using a 30° hammer angle. Tubes are operated during the test with  $E_f = 6.3$  volts,  $E_b = 150$  volts,  $E_{hk} = +100$  volts,  $R_g = 0.1$  meg, and  $R_k = 82$  ohms. Following the test, tubes are evaluated for low frequency vibrational output, heater-cathode leakage, heater current, and transconductance.

### Stability Life Test

The statistical sample subjected to the Intermittent Life Test is evaluated for percent change in transconductance of individual tubes, from the initial reading to readings following 2 hours and 20 hours of the life test.

### Survival Rate Life Test

The statistical sample subjected to the Intermittent Life Test is evaluated for shorted and open elements, and transconductance, following approximately 100 hours of life test.

### Intermittent Life Test

Statistical sample operated 1000 hours under the following conditions:  $E_f = 6.3$  volts,  $E_b = 150$  volts,  $E_{cc} = +6$  volts,  $E_{hk} = -70$  volts,  $R_k = 910$  ohms,  $R_g = 0.1$  meg. Heater voltage is cycled (on  $1\frac{3}{4}$  hours, off  $\frac{1}{4}$  hour). Tubes are evaluated, following 500 and 1000 hours of life test, for shorted or open elements, heater current, transconductance, heater-cathode leakage, and interelectrode leakage resistance.


### Interface Life Test

Statistical sample operated for 500 hours with  $E_f = 6.6$  volts, no other voltages applied, and evaluated for cathode interface resistance following the life test.


### Heater-Cycling Life Test

Statistical sample operated for 2000 cycles minimum to evaluate and control heater-cathode defects. Conditions of test include  $E_f = 7.0$  volts cycled for one minute on and one minute off,  $E_b = E_c = 0$  volts, and  $E_{hk} = 70$  volts with heater positive with respect to cathode. Following the test, tubes are evaluated for open heaters, heater-cathode shorts, and heater-cathode leakage.


### AVERAGE PLATE CHARACTERISTICS



### AVERAGE TRANSFER CHARACTERISTICS



### AVERAGE CHARACTERISTICS



RECEIVING TUBE DEPARTMENT

**GENERAL**  **ELECTRIC**

Owensboro, Kentucky