

MECHANICAL DATA

Bulb	T-6 $\frac{1}{2}$
Base	E9-1, Small Button 9-Pin
Outline	6-3
Basing	9H
Cathode	Coated Unipotential
Mounting Position Preferred	Upright or with Plate Majors in a Vertical Position
Permissible	Any

ELECTRICAL DATA

DIRECT INTERELECTRODE CAPACITANCES (Unshielded)

	Section 1	Section 2
Grid to Plate	6.0	6.0 μ f
Input: g to (h+k)	4.8	4.8 μ f
Output: p to (h+k)	0.65	0.55 μ f
Heater to Cathode	6.0	6.0 μ f
Grid No. 1 to Grid No. 2		0.10 μ f
Plate No. 1 to Plate No. 2		1.4 μ f

HEATER CHARACTERISTICS



	Series	Parallel
Heater Voltage	12.6 \pm 5%	6.3 \pm 5% Volts
Heater Current	450	900 Ma
Heater Power	5.7	5.7 Watts
Maximum Heater-Cathode Voltage		
Heater Negative with Respect to Cathode		
Total DC and Peak		200 Volts
Heater Positive with Respect to Cathode ¹		
DC		100 Volts
Total DC and Peak		200 Volts

RATINGS (Absolute Maximum Values—Each Section)²

Average Plate Voltage ³	300 Volts	Max.
Peak Plate Voltage (Measured Between Plate and Cathode) ⁴	600 Volts	Max.
Grid Voltage		
Negative Bias Value DC	100 Volts	Max.
Positive Bias Value DC	1.0 Volt	Max.
Peak Negative Value ⁴	300 Volts	Max.
Peak Positive Value ⁴	30 Volts	Max.
Average Positive Grid Current ³	5.0 Ma	Max.
Peak Positive Grid Current ⁴	200 Ma	Max.
Average Plate Dissipation ³	4.5 Watts	Max.
Average Total Plate Dissipation (Both Sections) ³	8.0 Watts	Max.
Average Cathode Current ³	50 Ma	Max.
Peak Cathode Current ⁴	400 Ma	Max.
Grid Circuit Resistance		
Fixed Bias	0.1 Megohm	Max.
Cathode Bias	0.47 Megohm	Max.
Bulb Temperature (At hottest point on bulb)	160° C	Max.

QUICK REFERENCE DATA

The Sylvania Type 7044 is a high-perveance, medium-mu, double triode designed primarily for computer applications. The tube is characterized by high zero-bias plate current and exceptional freedom from the development of cathode interface.



SYLVANIA ELECTRIC PRODUCTS INC.

RADIO TUBE DIVISION EMPORIUM, PA.

Prepared and Released By The TECHNICAL PUBLICATIONS SECTION EMPORIUM, PENNSYLVANIA

NOVEMBER, 1957

INITIAL CHARACTERISTICS (Each Section)⁵

Plate Voltage	120 Volts
Grid Voltage	-2 Volts
Plate Current	36 Ma
Transconductance	10,000 μ mhos
Amplification Factor	19
Plate Resistance	1900 Ohms
Grid Voltage for $I_b = 200 \mu a$ (approx.) at $E_b = 150V$	-12 Volts
Plate Current (Instantaneous Value) at $E_b = 90 Vdc$; E_c adjusted for $I_c = +250 \mu a$	50 Ma

INITIAL CHARACTERISTICS LIMITS (Range Values for Equipment Design)⁵

	Min.	Max.
Heater Current		
$E_f = 12.6$ Volts	410	490 Ma
Plate Current		
$E_f = 12.6$ Volts; $E_b = 90$ Volts; E_c Adjusted for $I_c = 250 \mu a$	41	62 Ma
Plate Current		
$E_f = 12.6$ Volts; $E_b = 120$ Volts; $E_c = -2$ Volts	26	45 Ma
Cutoff Plate Current		
$E_f = 12.6$ Volts; $E_b = 150$ Volts; $E_c = -14$ Volts	—	200 μa
Reverse Grid Current		
$E_f = 12.6$ Volts; $E_b = 120$ Volts; $E_c = -2$ Volts	—	1.5 μa
Heater-Cathode Leakage		
$E_f = 12.6$ Volts and $E_{hk} = \pm 100$ Volts	—	30 μa
Minimum Interelectrode Resistance (Except Heater-Cathode)		
Grid to All: Measured with 300 Volts, Grid Negative	50	— Megohms
Plate to All: Measured with 500 Volts, Plate Negative	50	— Megohms
Intermittent Leakage ⁶		


TIME DEPENDENT CHARACTERISTIC LIMITS⁵

	Min.	Max.
Cathode Interface		
$E_f = 12.6$ Volts; $E_b = 85$ Volts; E_c Adjusted for $I_b = 2.0$ Ma	—	25 Ohms
Number of Heater Cycles ⁷	2000	— Cycles


NOTES:

1. Heater positive not recommended for reliable operation.
2. Pulse terms in accordance with IRE Standards on Pulses: Definitions of Terms, Parts I and II, 1951, 1952.
3. Averaging time 1 millisecond unless otherwise specified.
4. A rectangular pulse is used of 10 μ sec width, 1% duty factor ($\pm 0.1\%$) and 1 kc repetition rate. The rise time shall be less than 1 μ sec and the fall time shall be less than 2 μ sec. Overshoot shall be less than 5% and droop shall be less than 10%.
5. Elements of the section not under test shall be grounded.
6. Intermittent leakage shall be measured with equipment capable of detecting resistances as follows:
 less than 1,000 ohms for 2 microseconds.
 less than 100,000 ohms for 15 microseconds.
 less than 2.5 megohms for 1 millisecond.
 The acceleration applied to the tube should be an approximate half sinusoid of 50 to 100 G for a base duration of approximately 500 Microseconds.
7. One cycle consists of operating the heater on for one minute, with $E_f = 15.0$ Volts, and off for four minutes. $E_{hk} = 140$ Vac, is applied continuously. The no load to steady state full load regulation of the heater voltage supply shall be no more than 3.0 percent.


AVERAGE PLATE CHARACTERISTICS



AVERAGE PLATE CHARACTERISTICS



AVERAGE TRANSFER CHARACTERISTICS



A Technical Publication of
**SYLVANIA ELECTRIC
PRODUCTS INC.**
EMPORIUM, PA.

