

BRIMAR VALVES

TYPE **25U4GT**

DATE ISSUED **9.7.51.**

R.M.A. REGISTRATION DATA

25U4GT DAMPER DIODE

The 25U4GT is a half wave rectifier especially designed for use as a damper diode in AC/DC television circuits. The electrical characteristics, except for the heater rating are similar to the 6U4GT.

MECHANICAL DATA.

Coated unipotential cathode
 Outline drawing 9-13 Bulb T-9
 Base B.6.8
 Maximum Diameter 1.9/32"
 Maximum Overall Length 3.3/8"
 Maximum Seated Height 2.13/16"
 Pin Connections Basing Number 4GG

Pin 1 - No connection	Pin 5 - Anode
Pin 2 - No connection	Pin 6 - -
Pin 3 - Cathode	Pin 7 - Heater
Pin 4 - -	Pin 8 - Heater

Mounting Position..... any

ELECTRICAL DATA.

Direct Inter-electrode Capacitance.

Cap. heater-cathode 8.5 μ f

RATINGS. (absolute maximum values)

Heater Voltage (ac or dc) 25 volts

Maximum heater-cathode voltage.

(a) Mains Rectifier

Heater positive with respect to cathode 385 volts
 Heater negative with respect to cathode 550 volts

(b) Damper Diode

Heater positive with respect to cathode	385 volts
* Heater negative with respect to cathode	3850 volts

Maximum Peak Inverse Voltage

(a) Mains Rectifier	1375 volts
* (b) Damper Diode	3850 volts

Maximum A.C. plate voltage (RMS)	375 volts
Maximum steady state peak plate current	860 mA
Maximum transient peak plate current	3.85 amps
(duration not exceeding 0.2 sec.)	
Tube voltage drop (measured with tube conducting 250 mA)	21 volts
Maximum D.C. output current	138 mA
Minimum total effective plate supply impedance	145 ohms

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS.

Heater voltage	25 volts
Heater current3 amps
A.C. Plate voltage (RMS)	350 volts
Filter Input capacitor	20 μ f
Total effective plate supply impedance	145 ohms
D.C. output current	125 mA
D.C. output potential	335 volts

- * This rating is applicable when the duty cycle of the voltage pulse does not exceed 15% of one scanning cycle and its duration is limited to 10 microseconds.